

## GL1500SE GOLD WING

### Colouring Concept

More than two decades in production, the Gold Wing continues its reign as the world's most popular luxury long-distance tourer.

Offering an unrivalled level of quality and comfort combined with the smooth, powerful performance of its famous 1,520cm<sup>3</sup> flat-six engine, the Gold Wing takes to the highways for 1999 in three elegant colour variations.

A light, all-new pearlescent green with dark green accents leads way with attractive style. Carried over from the previous year, are a lively

two-tone red and an urbane black with silver highlights that emphasizes the elegance of the Gold Wing's lines. Interior trim for all three variations is done entirely in black.

Also, to proudly commemorate Honda's 50th Anniversary of motorcycle production, this year's Gold Wing has been specially equipped with a set of commemorative emblems and a special ignition key that give an added air of exclusivity to Honda's most prestigious model.

### Colours

- Pearl Merced Green (with Dark Merced Green)
- Candy Spectra Red (with Candy Garnet Red)
- Black Z (with Pearl Twilight Silver)

### New Features

- Special Honda 50th Anniversary commemorative emblems.
- Special Honda 50th Anniversary commemorative key.
- New colour variation.
- Now meets EURO-1 exhaust emissions regulations.



*Specifications***Specifications****GL1500SE Gold Wing (ED-type)**

Engine	Liquid-cooled 4-stroke 12-valve SOHC horizontally opposed 6-cylinder
Bore × Stroke	71 × 64mm
Displacement	1,520cm <sup>3</sup>
Compression Ratio	9.8 : 1
Carburettors	33mm CV-type × 2
Max. Power Output	100PS/5,200rpm (DIN) (74kW/5,200min <sup>-1</sup> )
Max. Torque	15.3kg-m/4,000rpm (DIN) (150Nm/4,000min <sup>-1</sup> )
Ignition	Fully transistorized electronic
Starter	Electric
Transmission	5-speed
Final Drive	Enclosed shaft
Dimensions	(L×W×H) 2,615 × 955 × 1,495mm
Wheelbase	1,690mm
Seat Height	740mm
Ground Clearance	115mm
Fuel Capacity	23 litres
Wheels	Front/Rear Cast aluminium alloy
Tyres	Front 130/70-18 63H Rear 160/80-16 75H
Suspension	Front 41mm air-assist fork, 140mm axle travel Rear Single hydraulic damper with coil spring and single air spring, 105mm axle travel
Brakes	Front 296mm dual discs with dual-piston calipers and sintered metal pads Rear 316mm dual-piston caliper disc with sintered metal pads
Dry Weight	372kg

All specifications are provisional and subject to change without notice.

